

Appln No. 09/886,625

Amdt dat August 28, 2003

Reply to final Office action of February 28, 2003

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claims 1-4. (Canceled)

Claim 5. (Currently Amended) A positive coefficient device adapted for use in circuit protection, the device comprising:

a first laminar foil;

a second laminar foil; and

a polymeric compound between the first laminar foil and the second laminar foil, the polymeric compound comprising a polymer, a plasticizer between 5%-15% by volume of the polymeric compound, and two different carbon ~~black~~ blacks;

with the positive coefficient device having low room temperature resistivities and a switching temperature approximate 70 degrees Celsius.

Claim 6. (Original) The positive coefficient device of claim 5 wherein the polymer comprises a semi-crystalline polymer.

Claims 7-8. (Canceled)

Claim 9. (Currently Amended) A method of forming a low switching temperature polymeric positive temperature coefficient

Appln No. 09/886,625

Amdt dat August 28, 2003

Reply to final Office action of February 28, 2003

device suitable for circuit protection use, the method comprising:

compounding semi-crystalline polymer, plasticizer, and two different carbon black blacks, to form a polymeric compound, the plasticizer comprising approximately 10% by volume of the polymeric compound;

pressing the polymeric compound between nodular foil; and crosslinking the polymeric compound.

Claim 10. (Canceled)

Claim 11. (Currently Amended) The positive coefficient device of ~~claim 10~~ claim 5 wherein the plasticizer is a micronized polyester wax.

Claim 12. (Previously Presented) The positive coefficient device of claim 11 wherein the polymer is a semi-crystalline polymer.

Claim 13. (Previously Presented) The positive coefficient device of claim 12 wherein the polymer comprises between 30%-40% by volume of the polymeric compound.

Claim 14. (Previously Presented) The positive coefficient device of claim 13 wherein substantially most of the carbon black is of one type.

Appln No. 09/886,625

Amdt date August 28, 2003

Reply to final Office action of February 28, 2003

Claim 15. (Previously Presented) The positive coefficient device of claim 14 wherein the carbon blacks comprise greater than 5% by volume of the polymeric compound.

Claim 16. (Previously Presented) The positive coefficient device of claim 14 wherein the carbon blacks comprise 30% by volume of the polymeric compound.

Claim 17. (Previously Presented) The positive coefficient device of claim 14 wherein the carbon blacks comprise approximately 50% by volume of the polymeric compound.

Claims 18-33. (Canceled)

34. (Currently Amended) The method of forming the low switching temperature polymeric positive coefficient device of ~~claim 33~~ claim 9 wherein the two different carbon blacks comprise a first carbon black and a second carbon black, and the carbon black is substantially the first carbon black.